



Rustins QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 8/23/2023 Revision date: 8/23/2023 Supersedes version of: 8/23/2023 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Rustins QD Polyurethane Varnish Range
UFI : X300-D0AQ-900E-2KRH
Type of product : Paint
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : 55/999 Others
Function or use category : 55/999 Others

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Rustins Ltd
Waterloo road
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 - F +44 (0)208 452 2008
rustins@rustins.co.uk - rustins.ltd

Distributor

Excellence Ltd
43 Grange Parade,
Unit 43 Baldoyle Industrial Estate,
D13 Y860 Dublin
Ireland
T 00353 (0)1 8323300 - F 00353 (0)1 8323584
Orders@excellence.ie - www.excellence.ie

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16:30

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear eye protection, face protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
BUTYL DIGLYCOL substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 112-34-5 EC-No.: 203-961-6 EC Index-No.: 603-096-00-8 REACH-no: 01-2119475104-44	$\geq 1 - < 5$	Eye Irrit. 2, H319
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	CAS-No.: 25265-77-4	$\geq 1 - < 5$	Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact

: Wash skin with plenty of water.

First-aid measures after eye contact

: Rinse eyes with water as a precaution.

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

BUTYL DIGLYCOL (112-34-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-(2-Butoxyethoxy)ethanol
IOEL TWA	67.5 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	101.2 mg/m ³
IOEL STEL [ppm]	15 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Austria - Occupational Exposure Limits	
Local name	Butyldiglykol (Butoxydiethylenglykol; 2-(2-Butoxyethoxy)-ethanol; Diethylenglykolmonobutylether)
MAK (OEL TWA)	67.5 mg/m ³
MAK (OEL TWA) [ppm]	10 ppm
MAK (OEL STEL)	101.2 mg/m ³ (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	15 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	2-(2-Butoxyéthoxy)éthanol # 2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	2-(2-Бутокси-етокси) етанол
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanol; dietilen-glikol monobutil-eter
GVI (OEL TWA) [1]	67.5 mg/m ³
GVI (OEL TWA) [2]	10 ppm

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
KGVI (OEL STEL)	101.2 mg/m ³
KGVI (OEL STEL) [ppm]	15 ppm
Remark	Direktiva: 2006/15/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	2-(2-Boutoξuαιθοξυ)αιθανόλη
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	2-(2-Buthoxyethoxy)ethanol (Butyldiglykol)
PEL (OEL TWA)	70 mg/m ³
PEL (OEL TWA) [ppm]	10 ppm
NPK-P (OEL C)	100 mg/m ³
NPK-P (OEL C) [ppm]	15 ppm
Remark	I - dráždíl sliznice (oči, dýchací cesty), respektive kůže.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Butyldiglycol
OEL TWA [1]	68 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 202 af 21/02/2023
Finland - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanoli
HTP (OEL TWA) [1]	68 mg/m ³
HTP (OEL TWA) [2]	10 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)éthanol
VME (OEL TWA)	67.5 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	101.2 mg/m ³
VLE (OEL C/STEL) [ppm]	15 ppm

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-(2-Butoxyethoxy)ethanol
AGW (OEL TWA) [1]	67 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	1,5(I)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	2-(2-βουτοξυαιθοξυ) αιθανόλη
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	2-(2-BUTOXIETOXI)ETANOL
AK (OEL TWA)	67.5 mg/m ³
CK (OEL STEL)	101.2 mg/m ³
Remark	EU2 (2006/15/EK irányelvben közölt érték); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA [1]	67.5 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	101.2 mg/m ³

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
OEL STEL [ppm]	15 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	2-(2-Butossietossi)etanolo
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi) etanols (butildiglikols)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanolis (dietilenglikolio monobutileteris, oksidietanolio monobutileteris)
IPRV (OEL TWA)	67.5 mg/m ³
IPRV (OEL TWA) [ppm]	10 ppm
TPRV (OEL STEL)	101.2 mg/m ³
TPRV (OEL STEL) [ppm]	15 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	2-(2-butoxyéthoxy)éthanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
Netherlands - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
TGG-8u (OEL TWA)	50 mg/m ³
TGG-8u (OEL TWA) [ppm]	7.4 ppm
TGG-15min (OEL STEL)	100 mg/m ³
TGG-15min (OEL STEL) [ppm]	14.8 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	2-(2-Butoksyetoksy)etanol
NDS (OEL TWA)	67 mg/m ³
NDSCh (OEL STEL)	100 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi) etanol (éter dietilenoglicol monobutílico)
OEL TWA [ppm]	10 ppm FIV (Fração inalável e vapor)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi)-etanol/Dowanol DB
OEL TWA	67.5 mg/m ³ 10 mg/m ³
OEL STEL	101.2 mg/m ³ 15 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Serbia - Occupational Exposure Limits	
Local name	2-(2-бutoксиетокси)етанол; диетилен-гликол монобутил-етар
OEL TWA	68 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	ЕУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Butyldiglykol 2-(2-butoxyethoxy)etanol
NPHV (OEL TWA) [1]	67.5 mg/m ³
NPHV (OEL TWA) [2]	10 ppm

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
NPHV (OEL STEL)	101.2 mg/m ³
NPHV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanol (butildietilenglikol)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi) etanol (Dietilenglicol monobutiléter)
VLA-ED (OEL TWA) [1]	67.5 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	101.2 mg/m ³
VLA-EC (OEL STEL) [ppm]	15 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Dietylenglykolmonobutyleter
NGV (OEL TWA)	68 mg/m ³
NGV (OEL TWA) [ppm]	10 ppm
KTV (OEL STEL)	101 mg/m ³
KTV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
WEL TWA (OEL TWA) [1]	67.5 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	101.2 mg/m ³
WEL STEL (OEL STEL) [ppm]	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
Iceland - Occupational Exposure Limits	
Local name	2-(2-bútoxýetoxý)etanól (bútýldíglýkól)
OEL TWA	67.5 mg/m³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m³
OEL STEL [ppm]	15 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-2(butoksyetoksy)etanol
Grenseverdi (OEL TWA) [1]	68 mg/m³
Grenseverdi (OEL TWA) [2]	10 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	2-(2-бутоксietокси) етанол (бутилдиетиленгликол)
OEL TWA	67.5 mg/m³
OEL TWA [ppm]	10 ppm
KTV	1.5
Short time value [mg/m³]	101.25 mg/m³
Short time value [ppm]	15 ppm
Remark	(*) дополнување на граничната вредност заради донесената Директива на Комисијата 2006/15ES од 7 февруари 2006 за создавање на втора листа на индикативни гранични вредности за професионална изложеност според директивата 98/24/ЕС и за измените на директивата 91/322/ЕЕС и директивата 2000/39/ ЕС (Сл. весник бр. 38 од ден 9.2.2006, стр. 36); (KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m3 или во ml/m3(ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Butyldiglycol / Butyldiglykol [Diethylenglykolmonobutylether]
MAK (OEL TWA) [1]	67 mg/m³
MAK (OEL TWA) [2]	10 ppm
KZGW (OEL STEL)	101 mg/m³
KZGW (OEL STEL) [ppm]	15 ppm
Critical toxicity	Rein, Sang, Foie / Niere, Blut, Leber

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)

Notation	SS _C / SS _C
Regulatory reference	www.suva.ch, 01.01.2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Clear and colour range.
Odour	: Barely perceptible odour.

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: 0 °C
Boiling point	: > 100 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 7 – 9
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 120 – 150 mPa·s
Solubility	: Material highly soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.05
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)

LD50 dermal rabbit	2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645
Skin corrosion/irritation	: Not classified pH: 7 – 9
Serious eye damage/irritation	: Not classified pH: 7 – 9
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

BUTYL DIGLYCOL (112-34-5)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified

BUTYL DIGLYCOL (112-34-5)

Viscosity, kinematic	≈ 6.794 mm ² /s
----------------------	----------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

BUTYL DIGLYCOL (112-34-5)

LC50 - Fish [1]	1300 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

Organic solvent : Yes

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK)

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510)

: LGK 12 - Non-combustible liquids.

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for

: LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

Rusitns QD Polyurethane Varnish Range

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
Skin Sens. 1	Skin sensitisation, Category 1

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.